

BH-CSEC

Cold shrink end cap

Features/Applications:

BH-CSEC cold shrink end cap which made of EPDM rubber Simple and fast installation meeting a variety of configuration requirements. Providing sealing protection over multi-core cable ends Used to seal cable ends during installation or storage, protecting cable ends against moisture, contamination and corrosion.

- Simple and fast installation, no tools required.
- Accommodating size ranges from 13mm – 70mm.
- Sealing tight, high rebound even after prolonged years of aging and exposure.
- No mastic or tape required. No torches or heat required.
- Resists fungus, water, acids, alkalis and ozone.
- Easily removed, no training required for installation.
- Standard color: Black.



Technical Data

Property	Test Method	Standard Value
300% Modulus	ASTM D-412-75	4.2MPa
Ultimate Tensile	ASTM D-412-75	10.05MPa
Ultimate Elongation	ASTM D-412-75	600%
Tear strength	ASTM D-624C-73	28.3KN/m
Fungus Resistance	ASTM G-21	28 days exposure No Growth
Moisture Absorption 7 days@ 90°C in H ₂ O		3.0% wt. Gain

Product Dimensions (mm)

Modle No.	ID As Supplied (Min) /mm	ID after Recovered (Max) /mm	Wall Thickness after Recovered (Nom) /mm	Application Range (mm)	Length/mm (±10%)
BH-CSEC 70-20/12	Ø20	Ø12	2.5	Ø13- Ø16	70
BH-CSEC 70-28/16	Ø28	Ø16	2.5	Ø18- Ø24	70
BH-CSEC 70-47/23	Ø47	Ø23	2.6	Ø25- Ø38	70
BH-CSEC 70-80/46	Ø80	Ø46	2.6	Ø48- Ø70	70