


BH-CSB

Cold shrink breakout

Features/Applications:

BH-CSB cold shrink breakout which Made of liquid silicone rubber Simple and fast installation meeting a variety of configuration Requirements, Providing sealing protection over multi-core cable crutch, including 3-, 4-, 5-, 6-core breakouts

- Simple and fast installation, no tools required.
- Sealing tight, high rebound even after prolonged years of aging and exposure.
- No mastic or tape required. No torches or heat required.
- Resists fungus, water, acids, alkalis and ozone.
- Easily removed, no training required for installation.
- Standard color: Grey.



Product Dimensions (mm)

Model No.	Cores	ØC (As Supplied/ After Recovery)/mm	Application Range/mm	ØF (As Supplied/ After Recovery)/mm	Application Range/mm	Lr/mm	Lc/mm
BH-CSB-3-1	3	80/ 36	Ø38-Ø67	32/ 14	Ø16- Ø26	45	130
BH-CSB-3-2		88/ 43	Ø45-Ø78	35/ 16	Ø18- Ø29	45	135
BH-CSB-3-3		104/ 50	Ø52-Ø94	40/ 20	Ø22- Ø34	45	150
BH-CSB-3-4		120/ 59	Ø61-Ø110	47/ 23	Ø25- Ø41	45	165
BH-CSB-3-5		140/ 72	Ø74-Ø130	60/ 28	Ø30- Ø54	55	180
BH-CSB-3-5A1		150/ 72	Ø74-Ø140	65/ 28	Ø30- Ø59	55	180
BH-CSB- 3-5A2		165/ 72	Ø74-Ø155	70/ 28	Ø30- Ø64	55	180
BH-CSB-4-1	4	65/20	Ø22-Ø55	20/6	Ø8-Ø14	35	126
BH-CSB-4-2		80/28	Ø30-Ø70	25/8	Ø10-Ø19	40	137
BH-CSB-4-3		88/40	Ø42-Ø78	32/10	Ø12-Ø26	40	145
BH-CSB-4-4		120/45	Ø47-Ø110	47/15	Ø17-Ø41	40	145
BH-CSB-5-1	5	80/26	Ø28-Ø70	20/6	Ø8-Ø14	40	123
BH-CSB-5-2		88/36	Ø38-Ø78	25/8	Ø10-Ø19	40	134
BH-CSB-5-3		110/47	Ø49-Ø100	35/11	Ø13-Ø29	45	138
BH-CSB-5-3A		120/47	Ø49-Ø110	40/11	Ø13-Ø36	45	138
BH-CSB-6-1	6	104/35	Ø37-Ø94	32/10	Ø12- Ø26	60	135