

BH-CST

Cold shrink tubing

Features/Applications:

BH-CST cold shrink tubing which made of liquid silicone rubber offering good mechanical, insulation and sealing protection .Accommodating a wide range of cable sizes for indoor or outdoor applications.

- Simple and fast installation, no tools required.
- Sealing tight, high rebound even after prolonged years of exposure.
- No mastic or tape required. No torches or heat required.
- Resists fungus, water, acids, alkalis and ozone.
- Easily removed, no training required for installation.
- Standard color: Grey, black.



Product Dimensions (mm)

Product No.	ID as Supplied (Min) /mm	ID after Recovered (Max) /mm	Length after Recovered (Nom) /mm	Thickness after Recovered ($\pm 10\%$)/mm	Application Range (mm)
BH-CST-20/8	20	8	80 ~ 450	2 ± 0.2	$\varnothing 10 \sim \varnothing 16$
BH-CST-28/10	28	10	80 ~500	2.5 ± 0.2	$\varnothing 12 \sim \varnothing 20$
BH-CST-32/12	32	12	80 ~490	2.5 ± 0.2	$\varnothing 13.2 \sim \varnothing 22.4$
BH-CST-32/13	32	13	80 ~490	2 ± 0.2	$\varnothing 14 \sim \varnothing 24$
BH-CST-35/16	35	16	80 ~450	2 ± 0.2	$\varnothing 18 \sim \varnothing 29$
BH-CST-40/18	40	18	80 ~450	2 ± 0.2	$\varnothing 20 \sim \varnothing 34$
BH-CST-47/21	47	21	80 ~470	2 ± 0.2	$\varnothing 23 \sim \varnothing 41$
BH-CST-53/25	53	25	80 ~500	2 ± 0.2	$\varnothing 27 \sim \varnothing 47$
BH-CST-65/26	65	26	80 ~500	3 ± 0.2	$\varnothing 28 \sim \varnothing 50$
BH-CST-70/30	70	30	80 ~500	3 ± 0.2	$\varnothing 32 \sim \varnothing 60$
BH-CST-80/31	80	31	80 ~500	3 ± 0.2	$\varnothing 33 \sim \varnothing 72$
BH-CST-80/36	80	36	80 ~500	3 ± 0.2	$\varnothing 38 \sim \varnothing 72$
BH-CST-88/37	88	37	80 ~500	3 ± 0.2	$\varnothing 39 \sim \varnothing 80$
BH-CST-104/42	104	42	80 ~500	3 ± 0.2	$\varnothing 44 \sim \varnothing 94$
BH-CST-110/38	110	38	80 ~420	6 ± 0.2	$\varnothing 40 \sim \varnothing 100$
BH-CST-110/60	110	60	80~420	6 ± 0.2	$\varnothing 62 \sim \varnothing 100$