

BH-EPDM

EDMP cold shrink tube

Features/Applications:

BH-EPDM cold shrink tube which made of EPDM rubber Offering good mechanical, insulation and sealing protection. Accommodating a wide range of cable sizes for indoor or outdoor applications Simple and fast installation.

- Simple and fast installation, no tools required.
- Sealing tight, high rebound even after prolonged years of aging and exposure.
- No mastic or tape required. No torches or heat required.
- Resists fungus, water, acids, alkalis and ozone.
- Easily removed, no training required for installation.
- Standard color: Black.



Technical Data

Property	Test Method	Standard Value
300% Modulus	ASTM D-412-75	4.2MPa
Ultimate Tensile	ASTM D-412-75	10.05MPa
Ultimate Elongation	ASTM D-412-75	600%
Tear strength	ASTM D-624C-73	28.3KN/m
Fungus Resistance	ASTM G-21	28 days exposure No Growth
Moisture Absorption 7 days@ 90°C in H ₂ O		3.0% wt. Gain

Product Dimensions (mm)

Model No.	ID as supplied (Ø mm)	Length (mm)	Application OD Rang (Ømm)
BH-EPDM 152/20	20	152	8-15
BH-EPDM 178/20	20	178	8-15
BH-EPDM 178/25	25	178	10-20
BH-EPDM 203/25	25	203	10-20
BH-EPDM 280/25	25	280	10-20
BH-EPDM 305/25	25	305	10-20
BH-EPDM 254/32	32	254	12-26
BH-EPDM 280/32	32	280	12-26
BH-EPDM 305/32	32	305	12-26
BH-EPDM 152/35	35	152	12-26
BH-EPDM 203/35	35	203	12-26
BH-EPDM 230/35	35	230	12-26
BH-EPDM 280/35	35	280	12-26
BH-EPDM 152/40	40	152	17.5-33
BH-EPDM 203/40	40	203	17.5-33
BH-EPDM 254/40	40	254	17.5-33
BH-EPDM 305/40	40	305	17.5-33
BH-EPDM 457/40	40	457	17.5-33
BH-EPDM 152/53	53	152	25-46
BH-EPDM 178/53	53	178	25-46
BH-EPDM 203/53	53	203	25-46
BH-EPDM 254/53	53	254	25-46
BH-EPDM 305/53	53	305	25-46
BH-EPDM 457/53	53	457	25-46
BH-EPDM 152/70	70	152	32-63
BH-EPDM 230/70	70	230	32-63
BH-EPDM 305/70	70	305	32-63
BH-EPDM 355/70	70	355	32-63
BH-EPDM 457/70	70	457	32-63
BH-EPDM 230/104	104	230	43-94