

BH-CJK

Cold shrink joint kit 1-36KV

Features/Applications:

BH-CJK cold shrink joint kit is suitable for 1 or 3-core XLPE cable with Al or Cu conductor (1-36kV). The joint body is made of advanced liquid silicone rubber with integrated stress control. This design vouches for the best possible interface, thereby greatly minimizing partial discharge and improving its performance during operation. The joint kit includes all the necessary components to make the installation.

- Simple and fast installation, no tools required.
- Sealing tight, high rebound even after prolonged years of aging and exposure
- No mastic or tape required. No torches or heat required.
- Resists fungus, water, acids, alkalis and ozone.



Product Specification

Voltage U0/U (Um)	Cores	Cable Cross Section/mm2	Diameter over Insulation/mm	Product No.
26/35kV (36)	1, 3	35-50	22-28	18/30kV--BH-CJ-1/1(3/1)
		70-120	26.5-33	18/30kV--BH-CJ-1/2(3/2)
		150-240	31.5-39	18/30kV--BH-CJ-1/3(3/3)
		300-400	35.5-43	18/30kV--BH-CJ-1/4(3/4)
		500-630	40.5-49	18/30kV--BH-CJ-1/5(3/5)
12/20kV (24)	1, 3	25-50	18-22.5	12/20kV--BH-CJ-1/1(3/1)
		70-120	21-26.5	12/20kV--BH-CJ-1/2(3/2)
		150-240	25.5-32	12/20kV--BH-CJ-1/3(3/3)
		300-400	32.5-37	12/20kV--BH-CJ-1/4(3/4)
		500-630	39-44.5	12/20kV--BH-CJ-1/5(3/5)
8.7/15kV(17.5)	1, 3	25-50	16-19.5	8.7/15kV--BH-CJ-1/1(3/1)
		70-120	19-27.5	8.7/15kV--BH-CJ-1/2(3/2)
		150-240	23.5-30	8.7/15kV--BH-CJ-1/3(3/3)
		300-400	30.5-35	8.7/15kV--BH-CJ-1/4(3/4)
		500-630	37-42.3	8.7/15kV--BH-CJ-1/5(3/5)
6/10kV(12)	1, 3	50-70	16-19.5	6/10kV--BH-CJ-1/1(3/1)
		95-150	19-24.5	6/10kV--BH-CJ-1/2(3/2)
		185-300	23.5-30	6/10kV--BH-CJ-1/3(3/3)
		400-500	30.5-38	6/10kV--BH-CJ-1/4(3/4)
		630	37-42.3	6/10kV--BH-CJ-1/4(3/4)
0.6/1kV(1.2)	1, 3, 4, 5	25-50	—	0.6/1kV--BH-CJ-1(3,4,5)/1
		70-120		0.6/1kV--BH-CJ-1(3,4,5)/2
		150-240		0.6/1kV--BH-CJ-1(3,4,5)/3
		300-400		0.6/1kV--BH-CJ-1(3,4,5)/4