

BH-STT

Excellent tensile strength solder ring wire splice heat shrinkable tubing

Features/Applications:

BH-STT excellent tensile strength solder ring wire splice heat shrinkable tubing, one piece design, it consists of translucent improved polyolefine heat shrinkable tubing and fluxed solder. Provides insulation, inspection, strain relief and is waterproof. The color tube appear a proper wire size and makes installation easy and lowers the installed cost.

- Shrink ratio 3:1;
- Waterproof wiring splices;
- Translucent tubing provides precise inspection, easy control soldering process;
- Operating temperature range: -55° C--- +125° C;
- Fully recover temperature: +130°C;
- Staring melt temperature of solder : +125°C, fully melt temperature of solder: +150°C;
- Color: Red, Blue, Yellow, White as standard, other colors are available on request.



Product Dimensions (mm)



Part Number	Product Dimensions		Solder Ring Size(mm)		Max. Bundle Dia.(mm)	Standard Color
	ID(±0.1mm)	L(Max)	ID(±0.1mm)	W.T(±0.05mm)		
BH-STT-17	4.0	23	1.7	0.5	1.7	White
BH-STT-27	4.7	23	2.7	0.5	2.7	Red
BH-STT-45	5.7	40	4.5	0.55	4.5	Blue
BH-STT-60	6.7	40	6.0	0.60	6.0	Yellow