

BH-STG

General solder ring wire splice heat shrinkable tubing

Features/Applications:

BH-STG general solder ring wire splice heat shrinkable tubing, One piece design, it consists of transparent heat shrinkable tubing and fluxed solder. Provides insulation, inspection, strain relief and water proof. Makes installation easily and lower the installed cost. Color hot-melt glue on two ends of heat shrinkable tube, it very convenience to use exact wire dimension.

- Shrink ratio 2:1;
- Waterproof wiring splices;
- Transparent tubing provides precise inspection, easy control soldering process;
- Operating temperature range: -55° C--- +125° C;
- Minimum shrink temperature: +60°C, Minimum fully recover temperature: +110°C;
- Staring melt temperature of solder +125°C, fully melt temperature of solder: +150°C;
- Color: White,Red, Blue, Yellow, White as standard, other colors are available on request.



Product Dimensions (mm)

Part Number	Product Dimensions		Wire Dimensions(mm)			Cable Size	Standard Color	Reference TE's Part Number
	A(Min)	L(Max)	B(Min)	B(Max)/C(Max)	C(Min)	AWG(mm2)		
BH-STG-01	1.7	26.0	1.0	1.7	0.76	26~24(0.25~0.34)	White	CWT-9001
BH-STG-02-1	2.7	40.0	1.4	2.7	1.2	22~18(0.5~1.0)	Red	CWT-9002
BH-STG-02-2	2.7	18.5	1.4	2.7	1.2	22~18(0.5~1.0)	Blue	B-150-03-S
BH-STG-03-1	4.5	40.0	2.3	4.5	2	16~14(1.5~2.5)	Blue	CWT-9003
BH-STG-03-2	4.5	21.0	2.3	4.5	2	16~14(1.5~2.5)	Blue	B-150-05-S
BH-STG-03-3	4.5	30.0	2.3	4.5	2	16~14(1.5~2.5)	Blue	CWT-5
BH-STG-04-1	6.0	40.0	3.7	6.0	3.4	12~10(4.0~6.0)	Yellow	CWT-9004
BH-STG-04-2	7.0	41.5	3.7	7.0	3.8	12~10(4.0~6.0)	Yellow	CWT-9005
BH-STG-04-3	7.0	31.0	3.7	7.0	3.8	12~10(4.0~6.0)	Blue	CWT-7
BH-STG-04-4	7.0	20.0	3.7	7.0	3.8	12~10(4.0~6.0)	Blue	B-150-07-S
BH-STG-05	11.5	34.0	5.8	11.5	5.5	10~6(6.0~14.0)	Blue	CWT-11/B-150-11

- Heat shrinkable tubing
- Low temperature solder ring
- Waterproof hot melt adhesive

